



适用范围 The scope of application	适用于50米或50米以上各类船舶作夜间航行灯光信号联络作用。 Applied to the ships with the length 50m or above as lamp signal liaison when night navigation.				
名称 Name	右舷灯 Starboard light	左舷灯 Port light	桅灯 Masthead light	艉灯 Stern light	环照灯 All-round light
型号 Type	CXH1-11P	CXH2-11P	CXH3-11P	CXH4-11P	CXH6-11P
重量 Weight	3.2kg	3.2kg	3.2kg	3.2kg	3.2kg
颜色 Color	绿 Green	红 Red	白 White	白/黄 White/yellow	红/绿/白 Red/green/white
水平光弧 Level arc	112.5°	112.5°	225°	135°	360°
可见距离 Visibility	3n.m	3n.m	6n.m	3n.m	3n.m
电压 Voltage	24V	110V	220V		
功率 Power	60W	60W	65W		
发光强度 Luminous intensity	60cd				
灯头 Lamp holder	P28S				
防护等级 Protection class	IP56				
电缆外径 Cable outside Diameter	φ9				
材质 Material	工程塑料PA+GF High-strength engineering plastic PA+GF, PC, 不锈钢Stainless steel				
环境温度 Ambient temperature	-30℃ ~ 55℃				



该航行信号灯获得欧盟MED/EC证书。
The navigation signal obtained the EU MED/EC certificate